

galvanized conveyor belt hoods

**STANDARD
FULL HOOD**
with quick opening
hinge (open position)

**STANDARD
3/4 HOOD**
hinged (open one side)

**HEAVY DUTY
SUPPORT BANDS**

SMOOTH BOTTOM EDGE

**HEAVY DUTY
STEEL BASE PLATE**

**FIBERGLASS
AND
ALUMINUM
HOODS
ALSO
AVAILABLE**

**MAY BE BOLTED IN
OPEN OR CLOSED POSITION**

**LOCKING EYE-BOLTS WITH QUICK
OPENING WING NUTS (WING NUTS
ARE SUPPLIED AS STANDARD
EQUIPMENT)**

OUR STANDARD FULL HOOD is fabricated from heavy galvanized 22 ga. steel. The commercially dust and weather-tight shell provides full enclosure of material, belt, and idlers. Thoughtful construction permits easy access to all parts from either side of the belt. To service your equipment, simply loosen the wing nut on each lock bolt, raise the cover, and locate lock bolts in the Open Hood Retaining Bracket. This holds the hood in place until maintenance is complete.

THE STANDARD 3/4 HOOD is for those installations where maximum protection is desired but visibility and immediate access to one side is a must. 22 ga. steel hinged type is standard. 3/4 hoods are open on one side only.

Support bands are 12 ga. galvanized steel for hoods up to 36" wide hoods and 10 ga. bands on 42" and larger hoods. All bolts, nuts and washers are cad plated.



MATERIAL CONTROL, INC.

197 POPLAR PL. • UNIT 3
P.O. BOX 308
NORTH AURORA, IL 60542-0308

800-926-0376 • 630-892-4274 • FAX 630-892-4931

www.materialcontrolinc.com
e-mail: sales@materialcontrolinc.com